

# Dry Cutting Miter Saw – Electric



**90° and 45° cutting of thin metal plates, pipes, profiles and more – no deburring required**

**Premium Super Dry Cutter – 14" dia.**



### Model 9435 Max. Cutting Capacities

	90° Cut	45° Cut
Round	5.5"	4.72"
Square	4.92"	3.15"
Rectangular	4.13" x 6.1"	2.95" x 3.93"

### 6" max. depth of cut

- Cut stainless steel, ferrous and nonferrous metal, plastic and aluminum tubes, profiles and more – no deburring necessary
- Exclusive blade stabilizing system reduces vibration
- Powerful, high-torque motor for continuous operation
- Patented quick-release vise for precise bevel cuts

### Order No. 608302

Motor Power	15 Amp/110V*
Blade Diameter	14" (355mm)
Max. Depth of Cut	6" at 90°
Speed (Free)	1,600 RPM
Arbor Size	1"
Blade Part No.	724072 (14" dia.)
Blade No. of Teeth	72T
Weight	55 lbs.

\* 230V also available – Order No. 600301-220V

**9435 Premium Super Dry Cut Saw (608302) standard equipment includes saw blade (P/N 724072).**

Optional stand available – Part No. 600526T3



### 14" Saw Blades for Model 9435

P/N 724072, 72T,  
for construction

P/N 600570, 90T,  
for stainless and thin steel

P/N 600570SI, 90T,  
for stainless steel

P/N 600580, 72T,  
for stainless and medium steel

P/N 600590, 60T,  
for stainless and thick steel

P/N 600591, 60T,  
recommended for cast iron

P/N 600595, 66T,  
recommended for mild steel

P/N 600594, 96T,  
recommended for aluminum

DRY CUTTING SAWS

## Electric Nibblers & Shears

**Easily cut sheet metal and steel up to 3/8" thick**

- Ideal for cutting sheet metal, steel plate, weldments and double sheets
- Two-speed gearbox (model CS-3400-E)
- Head can be rotated to four 90° positions (selected models)
- Cut over 90° bends with optional die
- Ideal for use in underground storage tank removal, I-beam splitting, plate cutting and more



Contact us for information about Electric Shears

Model No.	Power	Working Speed (ft./min.)	Start Hole Dia.	Min. Radius	Strokes per Minute	Max. Sheet Thickness			Weight (lbs.)
						Mild Steel	Stainless Steel	Aluminum	
CS-350-E	12 Amp, 110V	4	1.25"	.280"	650	.135"	.090"	.135"	7.5
CS-500-E	12 Amp, 110V	4.5	1.25"	3.125"	600	.197"	.135"	.276"	8.5
CS-700-E	17.4 Amp, 110V	5	2.75"	5.5"	400	.276"	.197"	.394"	26
CS-3400-E*	17.4 Amp, 110V	5.2	3"	16"	230 / 370	.375"	.276"	.500"	32

\* 2-speed gearbox