

Giraffe® wall and ceiling sander with interchangeable head system

GE 7 + MH-T + SH

Order number 494.542



Technical attributes	
Power input	710 watt
Power output	410 watt
No load speed	1100-1650 rpm
Orbit rate, no load	3800-5700 opm
Sanding disc Ø	225 mm
Tool fixture	velcro
Tilt angle on the head	100 °
Length	1520 mm
Cable length	5,0 m
Weight	4,2 kg

Giraffe® wall and ceiling sander with interchangeable head system

- + Electronic: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- + Very handy, light-weight machine with optimum ease of operation. Provides comfortable and ergonomic working conditions
- + Fitted with innovative interchangeable head system. Sanding heads are attached and removed with a click
- + Triangular sanding head with a 4 mm stroke, ideal for sanding corners and edges. The orbital movement guides the abrasive directly up to the edge. The rotation follows the movement of the tool, without interruption of work
- + Easy guiding: by optimal balance between motor and sanding head
- + Reliable force transmission and high flexibility thanks to the flexible drive shaft from. For decades established "FLEX technology". Thanks to this design principle the weight on the head of the Giraffe is reduced to a minimum. This facilitates handling.
- + Gimbal-mounted sanding head provides high flexibility and optimum adjustment for sanding walls and ceilings.
- + Effective dust extraction from between the brush ring and the sanding pad prevents clogging of the abrasive and promotes a dust-free working environment
- + Option of connecting the FLEX safety vacuum cleaners to the FLEX clip-system on the guide tube
- + Dust-proof on/off switch
- + Very flexible thanks to an optional 500 mm extension (accessory) for high rooms, can be attached without any tools
- + According to the assortment of sanding paper ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting
- + Very large areas and rooms up to 3.40 m in height can be processed thanks to the optional application of the GM 340
- + The innovative, textile transport system allows the machine and accessories to be transported effortlessly. The Giraffe® does not have to be mounted and is immediately ready for use

Standard equipment	
1 triangular sanding head MH-T	457.191
1 clip-on quick clamping ring SH-FC 32	406.023
Antistatic suction hose 32 mm Ø x 4 m with snap coupling and coupling bush for vacuum cleaner, with auxiliary air control	406.708
1 carrying bag	408.867